ACCESS AND ENVIRONMENTAL CONSIDERATIONS FOR PEOPLE WITH DISABILITIES


KEY	
ES)	U n
F	S m


 Unsuitable for people with mobility equipment or needs
 Image: Comparison of the second se

Alternate facilities available

Alternate facilities are provided


KEY LOCATION CONSIDERATIONS







<image/>	 Door 1 (main door to classroom) External door 770mm wide Safety glass panel Lever handles standard height Adequate circulation space classroom side only Stairway 2 (rear access to classroom) 12 steps to main landing More than 1m wide Tread width and riser heights consistent except for threshold step No contrasting colour on Nosing Suitable handrail both sides Door 2 (landing to passageway) External doors 800mm wide Lever handle 1450 mm high Adequate circulation space stair landing only Passage way is 1150 mm wide Internal doorframe 850mm wide No door
----------	---

A Block - Ground Floor Office/Administration	Door (single entry) External door 110mm step to entry
	 Outward opening, 910mm width Security door inward opening Floor Surfaces Vinyl - slip resistant Lighting Adequate lighting Facilities Restricted circulation space Kitchenette facilities Internet access Visitor Sign in/registration bench and servery 940mm high and 620mm wide







Showers - Lay out for boys & girls are the same

- 110mm step to entry
 - $\circ \quad \text{Restricted circulation space}$
 - Narrow doors, self-closing
- No indicator bolt (occupied) on main entry door

Showers - Unisex

• As for boys & girls except it has a hob

Fixtures

- Hot & Cold taps, capstan handles, clearly identified
- Fixed shower head
- o Shelf for soap
- Shower curtain (not weighted)
- $\circ \quad \text{No seat or grab rails} \\$
- o No hob
- No handwashing facilities

Entry access

- Narrow doorway 780mm wide
- Threshold lip 30mm reduced to 15mm by non-slip mat
- Outward opening

Floor surfaces


Vinyl - non-slip

Lighting

o Adequate, recent upgrade

Cabin internal

- o Bunk beds only meets Australian standards.
- o 650mm headroom between upper and lower bunk
- Accessible from one side
- \circ $\;$ Access to the length of the bunk
- o Bunks can be moved
- \circ $\;$ Sufficient floor space to store mobility aids
- \circ $\;$ Storage under and adjacent to bunk
- Air-conditioning and fans available
- Power to charge PWC overnight



A block - Ground floor Kingfishers

accommodation





Stairway

- o Undercover
- 4 Steps timber, varying riser heights
- At least 1000mm wide, nosing accentuated
- Hand rails both sides
- Adequate lighting

Ramp


- Surfaces firm and slip resistant in all conditions
- o Handrails both sides & kerb
- At least 1000mm wide
- \circ covered,

gradient 1:14 (assisted MWC & PWC user)

Laundry

• Sink, washing machine, dryer and linen store Staff shower & toilet

- Inward opening door, level entry
- Lever handle indicator bolt
- o Slip resistant floor
- Shower curtain (not weighted) & glass screen, no hob
- Hanging shelf for soap
- No grab rail in shower
- Freestanding shower stool
- Handwashing facilities, soap & paper towel dispenser
- o Mirror
- o Standard toilet, no grab rails
- o Sanitary disposal unit




Stairway

- \circ exposed to weather
- 4 5 Steps timber, varying riser heights
- o Lower concrete step to ground
- At least 1000mm wide, nosing not accentuated
- Top & bottom of stairway has yellow raised threshold markers
- o Hand rails both sides, standard heights
- Adequate lighting

Veranda

- Wrap around veranda access to all bunk rooms, facilities in student accommodation & facilities
- o Undercover, non-slip timber
- o Adequate lighting at all times
- o 2.4m wide



- Sufficient floor space to store mobility aids
- Storage under and adjacent to bunk
- Air-conditioning and louvre windows available
- Power to charge PWC overnight

2 Bed Room

• Bunks only, unable to be moved


3 Bed Room

- Bunk bed and single bed
- Storage small MWC only
- 4 Bed Room
 - 2 Bunks only
 - Storage small MWC only

5 Bed Room

- 2 bunks & single bed, restricted access (less than length of bunk)
- o Unable to be moved
- No storage of mobility items
- Narrow doorway 800mm restricted circulation space in & outside bedroom door







Doorways

- Inward opening door 850mm, level entry,
- Adequate circulation space in and outside door
- Lever handle, no indicator bolt

Facilities

- Accessible shower
- Slip resistant, graded floor to waste outlet, no hob
- Shower curtain (not weighted)
- Fixed and portable shower seats
- Horizontal & vertical grab rails in shower
- Lever mixer tap, shower nozzle (can be hand held)
- No soap rack or dispenser in shower
- Handwashing sink has lever action mixer tap, mirror
- Soap and paper towel dispensers & towel rail
- Clearance under basin for w/c user,
- Standard toilet
- Horizontal & angle grab rail on left side
- Nappy & sanitary disposal units and a waste bin







Facilities - Bathroom, Toilet

- Shower over bathtub (no slip resistant fittings)
- $\circ \quad \ \ \text{Capstan taps and single faucet bathtub}$
- \circ \quad Capstan taps and fixed shower rose
- $\circ \quad \text{Hot and cold clearly indicated} \\$
- Shower screen and curtain
- Soap rack
- Hand basin with enclosed cabinet underneath, mirror and bench
- Basket with hand towels and 4 towel racks & hooks
- Toilet a non-standard pan, no grab rails, limited circulation space
- o Toilet paper dispenser high
- Sanitary disposal unit

Facilities - Dining Room

- Dining chairs and table
- o Limited kitchen facilities

Facilities - Laundry

• Sink, washing machine



Kitchen

- Floors slip resistant, even when wet
- Adequate lighting
- Benches stainless steel 900mm & 800mm height
- Adequate circulation space for small WC but no WC clearance under benches
- Essential items stored under benches
- All appliances identified, easy to use and clearly marked controls
- Handwashing basin, WC accessible, lever action tap, soap and paper towel dispenser

Indoor Dining Area

- Clear space to manoeuvre WC around tables
- Tables allow WC to be pushed underneath, fixed height 750mm above ground
- Chairs have backrest, no armrest 450mm seat height
- Air-conditioned and ceiling fans
- Servery No open area under for WC user
- Handwashing and dishwashing sinks in dining area not WC accessible, use hand basin in kitchen

Outdoor Dining Area

- \circ Floors timber, slip resistant even when wet
- Adequate lighting
- o Clear space to manoeuvre WC around tables
- Tables allow w/c to be pushed underneath, fixed height 750mm above ground
- Chairs have backrest, no armrest, 450mm seat height
- Ceiling fans
- Servery, stainless steel top, 900mm high
- No handwashing, use facilities in indoor dining area
- Pizza oven located adjacent to outdoor dining



Ramp


- Timber, firm and slip resistant in all conditions
- o Suitable handrails & kerb both sides
- o 1300mm wide
- Covered & adequate lighting
- Gradient 1:20 (independent MWC & PWC user)

Doorways

- Ramp entry doorway outward opening Threshold level with circulation space on both sides of door
- $\circ \quad \text{Lever door handles, lightly sprung} \\$
- o Glass panel in door

Stairways x3 (2 enter outdoor area, 1 to indoor areas

- Riser heights & tread widths are constant
- $\circ \quad \text{At least 1000mm wide} \\$
- o Slip resistant
- Nosing not accentuated
- $\circ \quad \ \ {\rm Suitable \ hand \ rails \ both \ sides}$
- $\circ \quad \text{Adequate lighting} \\$
- Mixed timber, metal & concrete steps and landings





Generally, wheelchair accessible with some carer assist if required

- Alternative equipment may be required for WC access over sand surfaces
- Visiting school to contact DEEC Principal prior to visit to support planning for students with diverse learning needs.
- Advisory teacher PI, HI, VI and therapists may be consulted to support planning for students with diverse needs prior to the camp

Fire Place

- Concrete block seating 500mm high for 50 60 formed in an elliptical ring around fire place
- Grass surrounds and sand/gravel within
- o Adequate lighting

